



Atorn High Grade Rust Loosener & Lubricant 300ML

Safety Data Sheet

1. Identification of Substance & Company

Product

Product name	Atorn High Grade Rust Loosener & Lubricant 300ML
Other names	Rust-Off Plus 300ML
Product code	6081520001
HSNO approval	Aerosols (Flammable) Group Standard 2006, HSR002515
UN number	1950
Packaging group	NA (Aerosol)
Hazchem code	1T
Poison schedule	Not allocated
Uses	Rust remover

Company Details

Company	EDL Fasteners LTD
Address	70 Richard Pearse Drive Mangere, Manukau New Zealand
Telephone	+64 9 257 5536
Fax	+64 9 257 5844
Website	www.edlfast.co.nz

Emergency Telephone Number: 0800-764 766

2. Hazard Identification

Hazard Classifications

This product has been approved under the Hazardous Substances and New Organisms Act (Aerosols (Flammable) Group Standard 2006, Approval HSR002515), and is classified as follows:

Classes:

- 2.1.2A flammable aerosol
- 6.1E acutely toxic by aspiration
- 6.3B mild skin irritant
- 6.4A eye irritant
- 9.1B highly toxic to the aquatic environment

SYMBOLS

DANGER



Other Classifications

There are no other classifications that are known to apply.

Hazard and Precautionary Statements

Hazard	Extremely flammable aerosol. May be harmful if swallowed and enters airways. Causes mild skin irritation. Causes eye irritation. Toxic to aquatic life with long lasting effects.
--------	---



Atorn High Grade Rust Loosener & Lubricant 300ML

Safety Data Sheet

Precautionary Read label before use.
Keep away from sparks/open flames/hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use."
Keep out of reach of children.
Wash hands thoroughly after handling.
Wear protective gloves/protective clothing. Wear eye/face protection."
Do not breathe spray.
Do not eat, drink or smoke when using this product.
Avoid release to the environment.

Further precautionary statements can be found in Section 4 – First Aid.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Class for ingredient(s)	Conc (% w/w)
Naphtha (petroleum), hydrotreated light	64742-49-0	3.1B, 6.1E (aspiration), 6.3B, 6.4A, 9.1B	70-85%
Isobutane	75-28-5	2.1.1A	5-12.5%
carbon dioxide	124-38-9	non hazardous	1.26-2.5%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

You should call the National Poisons Centre if you feel that you may have been harmed, or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

If medical advice is needed, have this MSDS, product container or label at hand. . If exposed or concerned: Get medical advice/ attention.

Recommended first aid facilities Ready access to running water is required. Accessible eyewash is recommended. Emergency shower, hand wash, soap. CPR training, oxygen mask.

Exposure

Swallowed IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Contact a doctor if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Apply continuous irrigation with water for at least 15 minutes holding eyelids apart. If symptoms persist, seek medical advice.

Skin contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. Take off contaminated clothing and wash before re-use.

Inhaled IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If patient is unconscious, place in the recovery position (on the side) for transport and contact a doctor. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Advice to Doctor

Treat symptomatically



Atorn High Grade Rust Loosener & Lubricant 300ML

Safety Data Sheet

5. Firefighting Measures

Fire and explosion hazards:	This product is a flammable aerosol. This product has the potential to cause fire or to create an additional hazard during fire.
Suitable extinguishing substances:	Carbon Dioxide, Water jet spray, Chemical powder, foam.
Unsuitable extinguishing substances:	High volume water jet.
Products of combustion:	Product may decompose in a fire and produce toxic or corrosive fumes. Hazardous decomposition products include carbon oxides, hydrocarbons, toxic pyrolysis products
Protective equipment:	Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.
Hazchem code:	1T (recommended, HAZCHEM signage not required)

6. Accidental Release Measures

Containment	If greater than 1000L is stored, secondary containment and emergency plans to manage any potential spills must be in place. Prevent product from entering environment.
Emergency procedures	In the event of a large spillage alert the fire brigade to location and give brief description of hazard. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain spill. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. If spray or gas escapes, increase ventilation.
Clean-up method	Collect product and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
Disposal	Mop up and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.
Precautions	Wear protective equipment to prevent skin and eye contamination and the inhalation of vapour. Work up wind or increase ventilation.

7. Storage & Handling

Storage	Avoid storage of harmful substances with food. Store out of reach of children. Containers should be kept closed in order to minimise contamination. Keep in a cool, dry place. Avoid contact with incompatible substances as listed in Section 10.
Handling	Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of vapour.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by the NZ Department of Labour for this product. There is a general limit of 10mg/m³ for dusts and mists when limits have not otherwise been established.

NZ Workplace Exposure Stds (OSH 2002)	Ingredient	WES-TWA	WES-STEL
	Naptha (petroleum) hydrotreated light	400ppm, 1600mg/m3 (Naphtha)	No data
	isobutane	simple ashyxiant	No data
	carbon dioxide	5000ppm 9000mg/m3	30000ppm 54000mg/m3



Atorn High Grade Rust Loosener & Lubricant 300ML

Safety Data Sheet

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety in Employment Act 1992 (HSE). Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



To protect eyes, it is recommended that goggles, safety glasses or full face mask be worn. Avoid wearing contact lenses.

Skin



Avoid repeated or prolonged skin contact. Wear overalls, rubber boots and impervious gloves, e.g. nitrile rubber, NBR gloves. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking. Wash hands after handling.

Respiratory

A respirator with an organic vapour cartridge when airborne concentrations approach the WES (section 8) should be used. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order.

WES Additional Information

No additional information

9. Physical & Chemical Properties

Appearance	brown liquid/aerosol
Odour	characteristic odour
pH	no data
Vapour pressure	0.42 kPa
Viscosity	no data
Boiling point	no data
Volatile materials	no data
Freezing / melting point	no data
Solubility	insoluble in water
Specific gravity / density	0.74
Flash point	-83°C (Isobutane)
Danger of explosion	When using: development of explosive vapour/air mixture possible.
Auto-ignition temperature	245 C
Upper and lower flammable limits	0.45 Vol %, 8.0 Vol %
Corrosiveness	not corrosive

10. Stability & Reactivity

Stability	This product is thermally stable when stored and used as directed.
Conditions to be avoided	Open flames, heat ignition sources.
Incompatible groups	Strong oxidising agents.
Hazardous decomposition products	None known.
Hazardous reactions	Heating aerosol can result in increase pressure and possible danger of explosion.



Atorn High Grade Rust Loosener & Lubricant 300ML

Safety Data Sheet

11. Toxicological Information

Summary

No specific data is available for this product. Where available, toxicological data has been researched and data for the mixture calculated. The results of these calculations are presented below. The product is considered to have the following toxicity:

Supporting Data

Acute	Oral	No data for mixture is available. Using the LD ₅₀ 's for the ingredients, the calculated LD ₅₀ (oral, rat) for the mixture is >5000mg/kg. Data considered includes: Naphtha (petroleum), hydrotreated light >5000mg/kg (rat). However the solvent is considered an acute oral toxicant by aspiration.
	Dermal	No data for mixture is available. Using LD ₅₀ 's for ingredients, the estimated LD ₅₀ (dermal, rat) for the mixture is >5,000 mg/kg.
	Inhaled	No data for mixture is available. Inhalation may cause drowsiness or dizziness. Using LC ₅₀ 's for ingredients, the estimated LC ₅₀ (inhalation, rat) for the mixture is >5,000 ppm. Data available includes: Naphtha (petroleum), hydrotreated light >12mg/L (rat), Naptha (petroleum) hydrotreated heavy >12mg/L (rat).
	Eye	The mixture is considered to be an eye irritant, because some of the ingredients present are considered eye irritants in more concentrated form.
Chronic	Skin	The mixture is considered to be a mild skin irritant, because some of the ingredients present are considered skin irritants in more concentrated form.
	Sensitisation	No data for mixture is available. No ingredient present at concentrations > 0.1% is considered a sensitizer.
	Mutagenicity	No data for mixture is available. No ingredient present at concentrations > 0.1% is considered a mutagen.
	Carcinogenicity	No data for mixture is available. No ingredient present at concentrations > 0.1% is considered a carcinogen.
	Reproductive / Developmental	No data for mixture is available. No ingredient present at concentrations > 0.1% is considered a reproductive or developmental toxicant or have any effects on or via lactation.
	Systemic	Inhalation may result in headaches, Dizziness, nausea, effects/damages to the central nervous system, narcotic effect and unconsciousness.
	Aggravation of existing conditions	None known.

12. Ecological Data

Summary

No specific data is available for this product. Where available, ecotoxicological data has been researched and data for the mixture calculated. The results of these calculations are presented below. The product is considered to have the following ecotoxicity groups:

Supporting Data

Aquatic	No data for mixture is available. Using EC ₅₀ 's for ingredients, the calculated EC ₅₀ for the mixture is between 1 mg/L and 10 mg/L and at least one of the components is either bioaccumulative or persistent in the aquatic environment. Data considered includes: Naphtha (petroleum), hydrotreated light 2.1 mg/L (96hr, Crustacea). Not rapidly biodegradable.
Bioaccumulation	Not applicable.
Degradability	Not applicable.
Soil	No data available for the mixture.
Terrestrial vertebrate	This product is not considered harmful to terrestrial vertebrates. No LC ₅₀ (diet) data for ingredients are available and the classification is based on the LD ₅₀ (oral) – see section 11 – oral toxicity.
Terrestrial invertebrate	The mixture is not considered harmful to terrestrial invertebrates.
Biocidal	Not applicable



Atorn High Grade Rust Loosener & Lubricant 300ML

Safety Data Sheet

Environmental effect levels:	Ingredients	EEL
	Naphtha (petroleum), hydrotreated light	Data unavailable
	Isobutane	Data unavailable
	Carbon Dioxide	Data unavailable

13. Disposal Considerations

Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.
Contaminated packaging	Send empty aerosol can to landfill or similar. Do not puncture or incinerate.

14. Transport Information

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Not considered a hazardous substance for transport.

UN number:	1950	Proper shipping name:	AEROSOLS
Class(es):	2	Packing group:	Not applicable
Precautions:	Flammable aerosol, ecotoxic	Hazchem code:	1T (recommended)

15. Regulatory Information

This product has been transferred to HSNO (Group standards), ERMA approval code:, Aerosols (Flammable) Group Standard 2006, HSR002515)

Specific Workplace Controls (as per HSNO approval referenced to Controls Matrix)

Key workplace requirements are:

MSDS	To be available within 10 minutes in workplaces storing >10L.
Labelling	No removal of labels and/or decanting of product into other containers can occur.
Emergency plan	Approved Evacuation Scheme required if > 1000L is stored.
Approved handler	Required if > 3000L is handled or stored. (Flammable aerosol)
Tracking	Not required.
Bunding and secondary containment	Required if > 1000L is stored.
Signage	Required if > 1000L is stored in any one location.
Test certificate	Required if > 3000L is stored in any one location.
Flammable zone	Must be established if > 3000L is stored in any one location.
Fire extinguisher	If > 3000L present.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health, Safety in Employment Act and Regulations, local Council Rules and Regional Council Plans.



Atorn High Grade Rust Loosener & Lubricant 300ML

Safety Data Sheet

16. Other Information

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
Approval Code	ERMA approval code:, Aerosols (Flammable) Group Standard 2006, HSR002515) Controls, ERMA. www.ermanz.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
Controls Matrix	List of default controls linking regulation numbers to Matrix code (e.g. T1, I16).
EC₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species).
ERMA	Environmental Risk Management Authority
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LD₅₀	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats).
MSDS	Material Safety Data Sheet (or Safety Data Sheet)
OSH	The Occupational Safety and Health Service of the Department of Labour (NZ)
UN Number	United Nations Number
WES	Workplace Exposure Standard

References

Data	Unless otherwise stated comes from the ERMA HSNO chemical classification information database (CCID) http://www.ermanz.govt.nz/hs/compliance/chemicals.html , for specific chemicals.
ERMA Transfer Gazettes Controls Matrix	Classifications and controls assigned for specific ingredients (consolidated gazette, 2004) Part of the ERMA New Zealand User Guide to the HSNO Control Regulations
WES 2002	The NZ Workplace Exposure Standards Effective from 2002, published by OSH and available on their web site – www.osh.dol.govt.nz .
Other References:	Würth NZ MSDS, ChemIDplus

Disclaimer

This MSDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The MSDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the MSDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. **The likely HSNO classifications for this MSDS have been estimated based on general information from the supplier (e.g., hazard, toxicological).** Full formulation details were not available. This MSDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the MSDS author, email info@datachem.co.nz or phone: **+64 9 940 30 80**.

